UT08-02F06

SCR

Pb-Free RoHS COMPLIANT

VOLTAGE:	600 Volts	CURRENT:	8 Ampers	Package:	TO-220F

FEATURES

- Highly dv/dt For High Reliability
- Low Thermal Resistance Increases Carrying Capacity
- Strongresistance To Electromagnetic Interference.
- With High Ability To Withstand The Shock Loading Of Large Current

TYPICAL APPLICATIONS

- Phase Control Operation Of Light Dimmers And Motor Speed Controllers
- ON/OFF Control Operation Of Heating Regulation And Induction Motor

Diagram:



Polarity:



PRODUCT SUMMARY

Gear	Value	Unit
I_{GT}Max.	0.2	mA
V_{DRM}/V_{RRM} Min.	600	V
$I_{T(RMS)}$	8	A

Absolute Maximum Ratings (Ta=25℃ Unless otherwise specified)

Parameter	Test Conditions	Symbol	Ratings	Unit
Repetitive Peak Off-State Voltage		V_{DRM}	600	V
Repetitive Peak Reverse Voltage		V_{RRM}	600	V
RMS On-State Current	Tc≤ 91 ℃	$I_{T(RMS)}$	8	A
Average On-State Current	Tc≤ 91 ℃	$I_{T(AV)}$	5	
Non Repetitive Surge Peak On-State Current	F= 50 Hz,Tp= 10 ms F= 50 Hz,Tp= 8.3 ms	I_{TSM}	70 77	A
I^2T Value For Fusing	Tp= 10 ms	I^2t	25	A
Critical Rate Of Rise Of On-State Current	IG=2*IGT, tr≤100ns F=100Hz,Tj=125℃	di/dt	50	A/μs
Peak Gate Current	Tp=20μs,Tj=125℃	I_{GM}	4	A
Average Gate Power Dissipation	Tj= 125 ℃	$P_{G(AV)}$	1.0	W
Maximum Mounting Torque	M3 srew	T_{MM}	1.1	N.m

Thermal Characteristcs (Ta=25℃ Unless otherwise specified)

Parameter	Test Conditions	Symbol	Typ.	Unit
Operating Junction Temperature Range		T_J	-40 to 125	℃
Storage Temperature Range		T_{STD}	-40 to 150	
Thermal Resistance Junction To Ambient With Steady-State	Still Air Environment With Ta=25℃	$R_{\theta JA}$	60	℃/W
Thermal Resistance Junction-Case With Steady-State	Device Mounted On 75mm x 45mm x 2.5mm Alu. Heat.	$R_{\theta JC}$	4.6	

UT08-02F06

SCR

Pb Pb-Free RoHS COMPLIANT

Electrical Characteristcs (Ta=25℃ Unless otherwise specified)

Parameter	Test Conditions	Symbol	Value			Unit
			Min.	Typ.	Max.	
Gate Trigger Current	V_D=12V,R_L=33Ω	I_{GT}	-	-	0.2	mA
Max. Gate Trigger Voltage	V_D=12V,R_L=33Ω	V_{GT}	-	-	0.8	V
Min. Gate Trigger Voltage	V_D =V_{DRM},T_j =125℃,R_L=3.3KΩ	V_{GD}	0.1	-	-	V
Holding Current	I_T= 50 mA	I_H	-	-	5.0	mA
Latching Current	I_G=1.2*I_{GT}	I_L	-	-	6.0	mA
Rise Of Off- State Voltage	V_D =2/3V_{DRM},T_j =125℃,Gate Open	dv/dt	5.0	-	-	V/us

Static Characteristcs (Ta=25℃ Unless otherwise specified)

Parameter	Test Conditions	Symbol	Value	Unit
Peak On-State Voltage	I_T= 16 A,Tp=380uS,Tj =25℃	V_{TM} $M_{AX.}$	1.6	V
Threshold Voltage	T_j =125℃	V_{TO} $M_{AX.}$	0.85	V
Dynamic resistance	T_j =125℃	R_D $M_{AX.}$	46	mΩ
Peak Repetitive Forward Blocking Current	V_D=V_{DRM} Tj =25℃	I_{DRM} $M_{AX.}$	5	uA
Peak Repetitive Reverse Blocking Current	V_R=V_{RRM} Tj =125℃	I_{RRM} $M_{AX.}$	1	mA

Model and identification instructions

UT 08 - 02 F 06

Productor Type
UT=SCR

Insulation Spec.:
A=Ins.=Insulation
Empty=No Ins.=No Insulation

$I_{T(RMS)}$ Spec.:
08=8A

"-"=Connection Symbol
Constant And Unchanging

IGT Spec.
02=0.2mA

Package Spec.:
F=TO-220F

VDRM/VRRM Spec.:
06=600V

Temperature Spec.:
Empty=Standard Temperature
H=high temperature

UT08-02F06

SCR

Pb Pb-Free RoHS COMPLIANT

Typical Characteristics Curves



Fig.1-RMS on-state current vs. case temperature



Fig.2- Maximum Power Dissipation Vs. on-state current



Fig.3-On-State Characteristics



Fig.4- Surge Peak On-state Current Vs. Number Cycles



Fig.5- Relative Variation Of Gate Trigger Current , Holding Current And Latching Current Versus Junction Temperature (Typical Value)



Fig.6- Non-repetitive surge peak on-state current for a sinusoidal pulse with width tp<20ms, and corresponding value of I2t (dI/dt<50A/μs)

UT08-02F06

SCR

Pb Pb-Free RoHS COMPLIANT

OUTLINE DRAWINGS

TO-220F



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	9.25	-	10.75	0.3642	-	0.4232
B	4.20	-	5.20	0.1654	-	0.2047
C	2.30	-	2.90	0.0906	-	0.1142
D	0.35	-	0.75	0.0138	-	0.0295
E	14.80	-	16.80	0.5827	-	0.6614
F	8.25	-	9.75	0.3248	-	0.3839
L	12.15	-	14.15	0.4783	-	0.5571
H	2.60	-	3.80	0.1024	-	0.1496
J	1.10	-	1.60	0.0433	-	0.0630
K	0.60	-	1.00	0.0236	-	0.0394
M	2.20	-	3.00	0.0866	-	0.1181
O	2.70	-	3.50	0.1063	-	0.1378
P	3.10	-	3.80	0.1220	-	0.1496

RECOMMEDNED LAYOUT DRAWINGS

TO-220F



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	1.60	-	-	0.0630	-
B	-	1.60	-	-	0.0630	-
C	-	2.54	-	-	0.1000	-
D	-	1.00	-	-	0.0394	-

UT08-02F06

SCR

Pb-Free RoHS COMPLIANT

MARKING INFORMATION



MARKING INSTRUCTIONS

NH=Niuhang Trademark

FF=Product Line Code,According To Actual Changes

YWW=Date Code,According To Actual Changes

LLWWF=Inernal Code,According To Actual Changes

UT08-02F06=Model

PACKING INFORMATION

Package Type	Package Code	Productor Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
TO-220F	P1	2.048	Tube	50	1000	5000

UT08-02F06

SCR

Pb Pb-Free RoHS COMPLIANT

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat−Temperature Min (TS min) −Temperature Max (TS max) −Time(ts min to ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: −Temperature (TL) − Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature (tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

Disclaimer

- Reproducing and modifying informatiom of the document is prohibited without permission from Niuhang Electronics Technology Co., LTD
- Niuhang Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Technology Co., LTD. does not assume any and all implied warranties,including warranties of fitness for particular purpose,non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.Customers are responsible in comprehending the suitable use in particular applications.Niuhang Electronics Technology Co., LTD.makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining,such as medical instruments.transportation equipment,aerospae machinery et cetera.Customers usin or selling these products for use in such applications do so at their own rish and agree to fully indemnify Niuhang Electronics Technology Co., LTD.for any damages resulting resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhang can not notify

UT08-02F06

SCR

Specification Revision History

Rev.	Date	Changed Items	Pre-Changed Content	Changed Content
A/1	2014-10-20	First Issue		
		Blank Below		