

BZT52B series
ZENER DIODE



Voltage: 2.4~75 Volts

P_D: 200 mW

Package: SOD-323

Features

- Low Zener Impedance
- Power Dissipation of 200mW
- High Stability and High Reliability
- Zener Voltage Tolerance: See Table-1

Mechanical Data

- Case: Molded With UL-94 ClassV-0 Recognized, RoHS-Compliant
- Polarity: Look At The Diagram And Polarity On The Right
- Terminals: Tin Plated Leads, Solderable Per J-STD-002 And JESD22-B102
- Mounting Position: Any

Diagram:



Polarity:



Single Phase, Half Wave, 60Hz, Resistive Or Inductive Load. For Capacitive Load, Derate Current By 20%


Maximum Ratings (Ta=25°C Unless Otherwise Specified)

Parameter	Symbol	Value	Unit
Power Dissipation	P _D	200	mW
Maximum Regulator Current	I _{ZM}	PD/VZ	mA

Thermal Characteristics (Ta=25°C Unless Otherwise Specified)

Parameter	Symbol	Value	Unit
Operating Temperature Range	T _{OPR}	-55 ~ 150	°C
Storage temperature range	T _{STG}	-55 ~ 150	°C

C-V Curve Chart



Symbol Instruction

Symbol	Instruction
I _F	Maximum Average Forward Rectified Current
V _F	Maximum Instantaneous Forward Voltage
V _R	Working Peak Reverse Voltage
I _R	Maximum Reverse Leakage Current @ V _{RWM}
V _Z	The Zener Voltage @ I _Z
I _{ZT}	The Zener Current @ V _Z

BZT52B series
ZENER DIODE

Table-1.ELECTRICAL CHARACTERISTICS (TA=25°C unless otherwise noted)

Device	MARK	Zener Voltage Range				Maximum Zener Impedance			Maximum Reverse Current	
		Vz@Izt			Izt	Zzt @Izt	Zzk @Izk	Izk	IR	VR
		Nom(V)	Min(V)	Max(V)	mA	Ω		mA	μ A	V
BZT52B2V4S	2WX	2.40	2.35	2.45	5	100	600	1.00	50.0	1.0
BZT52B2V7S	2W1	2.70	2.65	2.75	5	100	600	1.00	20.0	1.0
BZT52B3V0S	2W2	3.00	2.94	3.06	5	95	600	1.00	10.0	1.0
BZT52B3V3S	2W3	3.30	3.23	3.37	5	95	600	1.00	5.0	1.0
BZT52B3V6S	2W4	3.60	3.53	3.67	5	90	600	1.00	5.0	1.0
BZT52B3V9S	2W5	3.90	3.82	3.98	5	90	600	1.00	3.0	1.0
BZT52B4V3	2W6	4.30	4.21	4.39	5	90	600	1.00	3.0	1.0
BZT52B4V7S	2W7	4.70	4.61	4.79	5	80	500	1.00	3.0	2.0
BZT52B5V1S	2W8	5.10	5.00	5.20	5	60	480	1.00	2.0	2.0
BZT52B5V6S	2W9	5.60	5.49	5.71	5	40	400	1.00	1.0	2.0
BZT52B6V2S	2WA	6.20	6.08	6.32	5	10	150	1.00	3.0	4.0
BZT52B6V8S	2WB	6.80	6.66	6.94	5	15	80	1.00	2.0	4.0
BZT52B7V5S	2WC	7.50	7.35	7.65	5	15	80	1.00	1.0	5.0
BZT52B8V2S	2WD	8.20	8.04	8.36	5	15	80	1.00	0.7	5.0
BZT52B9V1S	2WE	9.10	8.92	9.28	5	15	100	1.00	0.5	6.0
BZT52B10S	2WF	10.00	9.80	10.20	5	20	150	1.00	0.2	7.0
BZT52B11S	2WG	11.00	10.78	11.22	5	20	150	1.00	0.1	8.0
BZT52B12S	2WH	12.00	11.76	12.24	5	25	150	1.00	0.1	8.0
BZT52B13S	2WI	13.00	12.74	13.26	5	30	170	1.00	0.1	8.0
BZT52B14S	2WY	14.00	13.72	14.28	5	25	110	1.00	0.1	10.5
BZT52B15S	2WJ	15.00	14.70	15.30	5	30	200	1.00	0.1	10.5
BZT52B16S	2WK	16.00	15.68	16.32	5	40	200	1.00	0.1	11.2
BZT52B18S	2WL	18.00	17.64	18.36	5	45	225	1.00	0.1	12.6
BZT52B20S	2WM	20.00	19.60	20.40	5	55	225	1.00	0.1	14.0
BZT52B22S	2WN	22.00	21.56	22.44	5	55	250	1.00	0.1	15.4
BZT52B24S	2WO	24.00	23.52	24.48	5	70	250	1.00	0.1	16.8
BZT52B27S	2WP	27.00	26.46	27.54	2	80	300	0.50	0.1	18.9
BZT52B30S	2WQ	30.00	29.40	30.60	2	80	300	0.50	0.1	21.0
BZT52B33S	2WR	33.00	32.34	33.66	2	80	325	0.50	0.1	23.1
BZT52B36S	2WS	36.00	35.28	36.72	2	90	350	0.50	0.1	25.2
BZT52B39S	2WT	39.00	38.22	39.78	2	130	350	0.50	0.1	27.3
BZT52B43S	2WU	43.00	42.14	43.86	2	130	350	0.50	0.1	29.4
BZT52B47S	2WV	47.00	45.83	48.17	2	170	1000	0.25	0.1	36.0
BZT52B51S	2X1	51.00	49.73	52.27	2	180	1300	0.25	0.1	39.0
BZT52B56S	D6	56.00	54.60	57.40	2	200	1400	0.25	0.1	43.0
BZT52B62S	2X3	62.00	60.45	63.55	2	225	1400	0.25	0.1	47.0
BZT52B68S	2X4	68.00	66.30	69.70	2	240	1600	0.25	0.1	52.0
BZT52B75S	2X5	75.00	73.13	76.87	2	265	1700	0.25	0.1	56.0

BZT52B series

ZENER DIODE



Typical Characteristics Curves




Fig.1-Power Dissipation Vs. Case Temp.




Fig.2-Forward Characteristics




Fig.3-Typical Reverse Characteristics




Fig.4-Typical Junction Capacitance




Fig.5-Zener Breakdown Characteristics





Fig.6-Effect Of Zener Voltage On Zener Impedance

BZT52B series
ZENER DIODE



OUTLINE DRAWINGS


SOD-323



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	2.40	-	2.70	0.0945	-	0.1063
B	1.55	-	1.85	0.0610	-	0.0728
C	1.15	-	1.45	0.0453	-	0.0571
D	0.75	-	1.10	-	-	0.0433
E	0.70	-	1.00	0.0276	-	0.0394
F	-	0.10	-	-	0.0039	-
G	0.25	-	0.55	0.0098	-	0.0217

RECOMMEDND LAYOUT DRAWINGS

SOD-323



OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	2.90	-	-	0.1142	-
B	--	0.50	--	--	0.0197	--
C	--	1.44	--	--	0.0567	--
D	--	0.73	--	--	0.0287	--

BZT52B series
ZENER DIODE



MARKING

MARKING INSTRUCTION



XXX=Make,.
White band denotes cathode

PACKING INFORMATION

Package Type	Package Code	Product Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
SOD-323	P1	0.0041	7" Reel	3000	45000	180000

BZT52B series


ZENER DIODE



Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (T _{smax} to T _p)	3°C/second max.	3°C/second max.
Preheat -Temperature Min(T _S min) -Temperature Max(T _S max) -Time(t _s min to t _s max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: -Temperature (T _L) - Time (t _L)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(T _P)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature(tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

BZT52B series

ZENER DIODE



Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Niuhan Electronics Technology Co., LTD
- Niuhan Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhan Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhan Electronics Technology Co., LTD. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Niuhan Electronics Technology Co., LTD. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, transportation equipment, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Niuhan Electronics Technology Co., LTD. for any damages resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to protect the customer's quality, change the internal structure and the production process Niuhan can not notify