

BT137F-600E



# FOUR-QUADRANTS TRIAC

**VOLTAGE:** 600 Volts

**CURRENT:** 8 Ampers

**Package:** TO-220F

## FEATURES

- Highly di/dt For High Reliability
- Low Thermal Resistance Increases Carrying Capacity
- High Commutation Capability
- Packages Are RoHS (2011/65/EU) Compliant


## TYPICAL APPLICATIONS

- Phase Control Operation Of Light Dimmers And Motor Speed Controllers
- ON/OFF Control Operation Of Heating Regulation And Induction Motor


## PRODUCT SUMMARY

| Gear                            | E   | Unit |
|---------------------------------|-----|------|
| $I_{GT(I-II-III)} \text{ Max.}$ | 10  | mA   |
| $I_{GTIV} \text{ Max.}$         | 25  |      |
| $V_{DRM}/V_{RRM} \text{ Min.}$  | 600 | V    |
| $I_{T(RMS)}$                    | 8   | A    |

## Diagram:



## Polarity:



## Absolute Maximum Ratings (Ta=25°C Unless otherwise specified)

| Parameter                                  | Test Conditions                                            | Symbol       | Ratings | Unit             |
|--------------------------------------------|------------------------------------------------------------|--------------|---------|------------------|
| Repetitive Peak Off-State Voltage          |                                                            | $V_{DRM}$    | 600     | V                |
| Repetitive Peak Reverse Voltage            |                                                            | $V_{RRM}$    | 600     | V                |
| RMS On-State Current                       | $T_c \leq 74^\circ\text{C}$                                | $I_{T(RMS)}$ | 8.0     | A                |
| Non Repetitive Surge Peak On-State Current | F= 50 Hz, $T_p= 20 \text{ ms}$                             | $I_{TSM}$    | 65      | A                |
|                                            | F= 50 Hz, $T_p= 16.6 \text{ ms}$                           |              | 71      |                  |
| $I^2T$ Value For Fusing                    | $T_p= 10 \text{ ms}$                                       | $I^2t$       | 24      | A                |
| Critical Rate Of Rise Of On-State Current  | $I_G=2 \cdot I_{GT}$ , $t_r \leq 100\text{ns}$ I - II -III | $di/dt$      | 80      | A/ $\mu\text{s}$ |
|                                            | F=100Hz, $T_j=125^\circ\text{C}$ IV                        |              | 40      |                  |
| Peak Gate Current                          | $T_p=20\mu\text{s}$ , $T_j=125^\circ\text{C}$              | $I_{GM}$     | 4.0     | A                |
| Average Gate Power Dissipation             | $T_j= 125^\circ\text{C}$                                   | $P_{G(AV)}$  | 0.5     | W                |
| Peak Gate Power Dissipation                |                                                            | $P_{GM}$     | 10.0    | W                |
| Maximum Mounting Torque                    | M3 srew                                                    | $T_{MM}$     | 1.1     | N.m              |

## Thermal Characteristics (Ta=25°C Unless otherwise specified )

| Parameter                                                   | Test Conditions                                      | Symbol          | Typ.       | Unit               |
|-------------------------------------------------------------|------------------------------------------------------|-----------------|------------|--------------------|
| Operating Junction Temperature Range                        |                                                      | $T_j$           | -40 to 125 | $^\circ\text{C}$   |
| Storage Temperature Range                                   |                                                      | $T_{STD}$       | -40 to 150 |                    |
| Thermal Resistance Junction To Ambient<br>With Steady-State | Still Air Environment<br>With $T_a=25^\circ\text{C}$ | $R_{\theta JA}$ | 60         | $^\circ\text{C/W}$ |
| Thermal Resistance Junction-Case<br>With Steady-State       | Device Mounted On<br>75mm x 45mm x 2.5mm Alu. Heat.  | $R_{\theta JC}$ | 4.5        |                    |

**BT137F-600E**

**FOUR-QUADRANTS TRIAC**
**Electrical Characteristics (Ta=25°C Unless otherwise specified )**

| Parameter                  | Test Conditions                                      | Symbol   | Quadrant         | Value |          | Unit |
|----------------------------|------------------------------------------------------|----------|------------------|-------|----------|------|
|                            |                                                      |          |                  | Gear  | E        |      |
| Gate Trigger Current       | $V_D=12V, R_L=33\Omega$                              | $I_{GT}$ | I - II-III<br>IV | Max.  | 10<br>25 | mA   |
| Max. Gate Trigger Voltage  | $V_D=12V, R_L=33\Omega$                              | $V_{GT}$ | ALL              | Max.  | 1        | V    |
| Min. Gate Trigger Voltage  | $V_D=V_{DRM}, T_j=125^\circ C, R_L=3.3K\Omega$       | $V_{GD}$ | ALL              | Min.  | 0.2      | V    |
| Holding Current            | $I_T=500\text{ mA}$                                  | $I_H$    |                  | Max.  | 20       | mA   |
| Latching Current           | $I_G=1.2 \cdot I_{GT}$                               | $I_L$    | I -III-IV<br>II  | Max.  | 20<br>35 | mA   |
| Rise Of Off- State Voltage | $V_D=2/3 V_{DRM}, T_j=125^\circ C, \text{Gate Open}$ | $dv/dt$  |                  | Min.  | 250      | V/us |

**Static Characteristics (Ta=25°C Unless otherwise specified )**

| Parameter                                | Test Conditions   | Symbol    | $T_j$ | Value |      | Unit |
|------------------------------------------|-------------------|-----------|-------|-------|------|------|
| Peak On-State Voltage                    | $I_T=10\text{ A}$ | $V_{TM}$  | 25°C  | Max.  | 1.5  | V    |
| Threshold Voltage                        |                   | $V_{TO}$  | 125°C | Max.  | 0.8  | V    |
| Dynamic resistance                       |                   | $R_D$     | 125°C | Max.  | 53   | mΩ   |
| Peak Repetitive Forward Blocking Current | $V_D=V_{DRM}$     | $I_{DRM}$ | 25°C  | Max.  | 5    | uA   |
|                                          | $V_D=V_{DRM}$     |           | 125°C |       | 0.35 | mA   |
| Peak Repetitive Reverse Blocking Current | $V_R=V_{RRM}$     | $I_{RRM}$ | 25°C  | Max.  | 5    | uA   |
|                                          | $V_R=V_{RRM}$     |           | 125°C |       | 0.35 | mA   |

**Model and identification instructions**

|                                                                        |     |   |   |     |   |
|------------------------------------------------------------------------|-----|---|---|-----|---|
| BT                                                                     | 137 | F | - | 600 | E |
| Product Type<br>BT=TRIAC                                               |     |   |   |     |   |
| Insulation Spec.:<br>A=Ins.=Insulation<br>Empty=No Ins.=No Insulation  |     |   |   |     |   |
| $I_{T(RMS)}$ Spec.:<br>137=8A                                          |     |   |   |     |   |
| Package Spec.:<br>F=TO-220F                                            |     |   |   |     |   |
| "-."=Connection Symbol<br>Constant And Unchanging                      |     |   |   |     |   |
| $V_{DRM}/V_{RRM}$ Spec.:<br>600≅600V                                   |     |   |   |     |   |
| $I_{GT}$ Spec.:<br>E:IGT I - II -III ≅ 10mA;IGT IV ≅ 25mA              |     |   |   |     |   |
| Temperature Spec.:<br>Empty=Standard Temperature<br>H=high temperature |     |   |   |     |   |

BT137F-600E

FOUR-QUADRANTS TRIAC



### Typical Characteristics Curves




Fig.1-RMS on-state current vs. case temperature




Fig.2- Maximum Power Dissipation Vs. on-state current




Fig.3-On-State Characteristics




Fig.4- Surge Peak On-state Current Vs. Number Cycles




Fig.5- Relative Variation Of Gate Trigger Current , Holding Current And Latching Current Versus Junction Temperature (Typical Value)





Fig.6- Non-repetitive surge peak on-state current for a sinusoidal pulse with width  $t_p < 20\text{ms}$ , and corresponding value of  $I_2t$  ( $dI/dt < 50\text{A}/\mu\text{s}$ )

BT137F-600E



FOUR-QUADRANTS TRIAC


OUTLINE DRAWINGS



TO-220F

| OUTLINE DIMENSIONS |            |      |       |        |      |        |
|--------------------|------------|------|-------|--------|------|--------|
| Dim.               | Milimeters |      |       | Inches |      |        |
|                    | Min.       | Typ. | Max.  | Min.   | Typ. | Max.   |
| A                  | 9.25       | -    | 10.75 | 0.3642 | -    | 0.4232 |
| B                  | 4.20       | -    | 5.20  | 0.1654 | -    | 0.2047 |
| C                  | 2.30       | -    | 2.90  | 0.0906 | -    | 0.1142 |
| D                  | 0.35       | -    | 0.75  | 0.0138 | -    | 0.0295 |
| E                  | 14.80      | -    | 16.80 | 0.5827 | -    | 0.6614 |
| F                  | 8.25       | -    | 9.75  | 0.3248 | -    | 0.3839 |
| L                  | 12.15      | -    | 14.15 | 0.4783 | -    | 0.5571 |
| H                  | 2.60       | -    | 3.80  | 0.1024 | -    | 0.1496 |
| J                  | 1.10       | -    | 1.60  | 0.0433 | -    | 0.0630 |
| K                  | 0.60       | -    | 1.00  | 0.0236 | -    | 0.0394 |
| M                  | 2.20       | -    | 3.00  | 0.0866 | -    | 0.1181 |
| O                  | 2.70       | -    | 3.50  | 0.1063 | -    | 0.1378 |
| P                  | 3.10       | -    | 3.80  | 0.1220 | -    | 0.1496 |

RECOMMEDND LAYOUT DRAWINGS



TO-220F

| OUTLINE DIMENSIONS |            |      |      |        |        |      |
|--------------------|------------|------|------|--------|--------|------|
| Dim.               | Milimeters |      |      | Inches |        |      |
|                    | Min.       | Typ. | Max. | Min.   | Typ.   | Max. |
| A                  | -          | 1.60 | -    | -      | 0.0630 | -    |
| B                  | -          | 1.60 | -    | -      | 0.0630 | -    |
| C                  | -          | 2.54 | -    | -      | 0.1000 | -    |
| D                  | -          | 1.00 | -    | -      | 0.0394 | -    |

BT137F-600E



FOUR-QUADRANTS TRIAC

MARKING INFORMATION



MARKING INSTRUCTIONS

NH=Niuhang Trademark  
FF=Product Line Code,According To Actual Changes  
YWW=Date Code,According To Actual Changes  
LLWWF=Inernal Code,According To Actual Changes  
BT137F-600E=Model

PACKING INFORMATION

| Package Type | Package Code | Product Weight Approx(g/Pcs) | Package Method | Quantity (Pcs/Min. Pack.) | Quantity (Pcs/Inner Box) | Quantity (Pcs/Carton) |
|--------------|--------------|------------------------------|----------------|---------------------------|--------------------------|-----------------------|
| TO-220F      | P1           | 2.048                        | Tube           | 50                        | 1000                     | 5000                  |

BT137F-600E



# FOUR-QUADRANTS TRIAC

## Recommended wave soldering condition

| Product         | Peak Temperature | Soldering Time  |
|-----------------|------------------|-----------------|
| Pb-free devices | 260 +0/-5 °C     | 5 +1/-1 seconds |

## Recommended temperature profile for IR reflow

|  | Profile feature                                                                                                  | Sn-Pb eutectic Assembly          | Pb-free Assembly                 |
|--|------------------------------------------------------------------------------------------------------------------|----------------------------------|----------------------------------|
|  | Average ramp-up rate (T <sub>smax</sub> to T <sub>p</sub> )                                                      | 3°C/second max.                  | 3°C/second max.                  |
|  | Preheat-Temperature Min (T <sub>S</sub> min)<br>-Temperature Max (T <sub>S</sub> max)<br>-Time(ts min to ts max) | 100°C<br>150°C<br>60-120 seconds | 150°C<br>200°C<br>60-180 seconds |
|  | Time maintained above:<br>-Temperature (T <sub>L</sub> )<br>- Time (t <sub>L</sub> )                             | 183°C<br>60-150 seconds          | 217°C<br>60-150 seconds          |
|  | Peak Temperature(T <sub>P</sub> )                                                                                | 240 +0/-5 °C                     | 260 +0/-5 °C                     |
|  | Time within 5°C of actual peak temperature (t <sub>p</sub> )                                                     | 10-30 seconds                    | 20-40 seconds                    |
|  | Ramp down rate                                                                                                   | 6°C/second max.                  | 6°C/second max.                  |
|  | Time 25 °C to peak temperature                                                                                   | 6 minutes max.                   | 8 minutes max.                   |
|  |                                                                                                                  |                                  |                                  |

Note : All temperatures refer to topside of the package, measured on the package body surface.

## Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Niuhang Electronics Technology Co., LTD
- Niuhang Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Technology Co., LTD. does not assume any and all implied warranties,including warranties of fitness for particular purpose,non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.Customers are responsible in comprehending the suitable use in particular applications.Niuhang Electronics Technology Co., LTD.makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining,such as medical instruments,transportation equipment,aerospae machinery et cetera.Customers usin or selling these products for use in such applications do so at their own rish and agree to fully indemnify Niuhang Electronics Technology Co., LTD.for any damages resulting resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhang can not notify

BT137F-600E

FOUR-QUADRANTS TRIAC



Specification Revision History

| Rev.        | Date       | Changed Items | Pre-Changed Content | Changed Content |
|-------------|------------|---------------|---------------------|-----------------|
| A/1         | 2014-10-20 | First Issue   |                     |                 |
| Blank Below |            |               |                     |                 |