NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Voltage:	750	Volts	Current:	10.0	Ampers	Package:	TO-247


Features

- NH'S Advanced Silicon Carbide MOSFET Technology
- High Blocking Voltage And Low Capacitances
- High-Speed Switching For Very Low Switching Losses
- Excellent Qg*Rds(on) Product(FOM）


Typical Applications

- High Voltage DC/DC Converters
- Adaptor And Charger
- Battery Chargers And Motor Drives
- LED Drives And LED Lighting

Diagram:



Polarity:



Product Summary

VDS Min.@T_j	750	**V**
I_D Min.@Ta	10.0	**A**
RDS(ON)(TYP)@18V,Tj=25℃	260	**mΩ**

***100% UIS TESTED**

***100% ΔVDS TESTED**

Absolute Maximum Ratings (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Ratings	Unit
Drain-Source Voltage		V_{DS}	750	V
Gate-Source Voltage		$V_{GS\ MAX.}$ $V_{GS\ O.P.}$	-10/+22 0/+15 or 18	V
Continuous Drain Current (Note 1)	Ta= 25 ℃ Ta= 100 ℃	I_D	10.0 8.0	A
Drain Current-Pulse (Note 1)	T_J< 175 ℃	I_{DM}	18	A
Maximum Power Dissipation Power Dissipation Derating Factor Above 25℃	Ta= 25 ℃ Ta= 100 ℃	P_D	278 139	W
Derating Factor		D_F	1.85	W/℃
Avalanche Current,Single Pulse (Note 1)	L= 0.5 mH	I_{AS}	8.2	A
Single Pulse Avalanche Energy (Note 1) Test Circuit & Waveform See Fig.22	L= 0.5 mH IAS= 8.2 A,RG= 10.0 Ω Starting Tj=25 ℃,VG = 18.0 V	E_{AS}	16.8	mJ

Thermal Characteristcs (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions	Symbol	Typ.	Unit
Junction Temperature		T_J	-55 to 175	℃
Storage Temperature Range		T_{STD}	-55 to 175	℃
Thermal Resistance Junction To Ambient With Steady-State	Still Air Environment With Ta=25℃	$R_{\theta JA}$	50	℃/W
Thermal Resistance Junction-Case With Steady-State	Device Mounted On 75mm x 45mm x 2.5mm Alu. Heat.	$R_{\theta JC}$	0.54	

Notes: 1.Pulse Width Limited By Max. Junction Temperature. (See Fig. 19).

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Electrical Characteristcs (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions		Symbol	Min.	Typ.	Max.	Unit
Static Off Characteristics							
Drain-Source Breakdown Voltage	VGS=0V,ID=100uA		BV_{DSS}	750	--	--	V
Zero Gate Voltage Drain Current	VDS= 0 V,VGS=0V,Tj=25℃		I_{DSS}	--	0.1	20	uA
	VDS= 750 V,VGS=0V,Tj=175℃			--	3	--	
Gate To Source Leakage Current	VGS= 22 V,VDS=0V		I_{GSS}	--	--	250	nA
Source To Gate Leakage Current	VGS= -10 V,VDS=0V		I_{SGS}	--	--	250	nA
Forward Transconductance	ID= 3.5 A,VDS= 20 V		gfs	--	2.9	--	S
Static On Characteristics							
Gate Threshold Voltage	VGS= VDS, ID=10mA ,Tj=25℃		$V_{GS(TH)}$	3	3.7	5	V
	VGS= VDS, ID=10mA ,Tj=175℃			--	2.7	--	
Drain-Source On Resistance	ID= 3.5 A,VGS= 18.0 V,Tj=25℃		$R_{DS(ON)}$	--	260	300	mΩ
	ID= 3.5 A,VGS= 18.0 V,Tj=175℃			--	302	330	
	ID= 3.5 A,VGS= 15.0 V,Tj=25℃			--	338	450	
	ID= 3.5 A,VGS= 15.0 V,Tj=175℃			--	365	486	
Dynamic Characteristics							
Input Capacitance	VDS= 650 V		C_{iss}	--	223	--	pF
Output Capacitance	VGS= 0 V		C_{oss}	--	22	--	pF
Reverse Transfer Capacitance	F= 1 MHZ		C_{rss}	--	3.5	--	pF
Gate Resistance	VGS=0V,VDS=0V,Freq.=1MHz		R_g	--	26	--	Ω
Switching Paramters (Test Circuit & Waveform See Fig.20)							
Turn-On Delay Time	VDS= 400 V ID= 3.5 A	Tj=25℃	$t_{d(on)}$	--	11	--	ns
		Tj=175℃		--	10.5	--	
Turn-On Rise Time	VGS= 0/+18 V RG= 10.0 Ω	Tj=25℃	t_r	--	7.5	--	ns
		Tj=175℃		--	7.1	--	
Turn-Off Delay Time	L= 600 μH	Tj=25℃	$t_{d(off)}$	--	8	--	ns
		Tj=175℃		--	7.6	--	
Turn-Off Rise Time		Tj=25℃	t_f	--	5	--	ns
		Tj=175℃		--	4.3	--	
Turn−On Switching Loss		Tj=25℃	E_{on}	--	12.9	--	μJ
		Tj=175℃		--	12.3	--	
Turn−Off Switching Loss		Tj=25℃	E_{off}	--	9.1	--	μJ
		Tj=175℃		--	8.3	--	
Total Switiching Energy		Tj=25℃	E_{tot}	--	22.0	--	μJ
		Tj=175℃		--	20.6	--	

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Electrical Characteristcs (Ta=25℃ Unless Otherwise Specified)

Parameter	Test Conditions		Symbol	Min.	Typ.	Max.	Unit
Gate Charge Paramters (Test Circuit & Waveform See Fig.21)							
Total Gate Charge	VDS= 400 V		Q_g	--	9	--	nC
Gate-Source Charge	VGS= 0/+18 V		Q_{gs}	--	3.5	--	nC
Gate-Drain Charge	ID= 3.5 A		Q_{gd}	--	1.2	--	nC
Drain-Source Diode Characteristics And Maximum Ratings (Test Circuit & Waveform See Fig.23)							
Max. Diode Forward Cuurent	Tj= 25 ℃		I_S	--	--	10.0	A
tp Limited by T_J(max)	Tj= 100 ℃			--	--	8.0	
Max. Pulsed Forward Cuurent			I_{SM}	--	--	15	A
Diode Forward Voltage	ID= 3.0 A,VGS=-0V	Tj=25℃	V_{SD}	--	3.5	--	V
		Tj=175℃		--	3.0	--	
Reverse Recovery Time	IS= 5.0 A di/dt= 1000.0 A/us	Tj=25℃	t_{rr}	--	9.2	--	ns
		Tj=175℃		--	10.4	--	
Reverse Recovery Charge	VGS= 0.0 V VDS= 400 V	Tj=25℃	Q_{rr}	--	25	--	nC
		Tj=175℃		--	28.8	--	
Reverse Recovery Current		Tj=25℃	I_{rrm}	--	5.0	--	A
		Tj=175℃		--	5.5	--	
Reverse Recovery Energy		Tj=25℃	E_{rr}	--	9.2	--	μJ
		Tj=175℃		--	11.5	--	

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Typical Characteristics Curves




Fig.1-Output Characteritsics@Tj=25℃




Fig.2-Output Characteritsics@Tj=175℃




Fig.3-On Resistance Vs. Drain Current




Fig.4-On Resistance Vs. Gate Source Voltage




Fig.5-On Resistance Vs. Junction Temperature




Fig.6-Breakdown Voltage Vs. Junction Temperature

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Typical Characteristics Curves




Fig.7-Gate Source Threshold Voltage Vs. Junction Temperature




Fig.8-Transfer Characteritsics




Fig.9-Typical Switching Energy Vs. Junction Temperature




Fig.10-Typical Switching Energy Vs. External Gate Resistance




Fig.11-Typical Switching Energy Vs. Drain Source Current




Fig.12-Typical Switching Energy Vs. Drain Source Voltage

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Typical Characteristics Curves




Fig.13-Maximum Continuous Drain Current Vs. Case Temperature




Fig.14-Maximum Power Dissipation Vs. Case Temperature




Fig.15-Source-To-Drain Diode Forward Voltage




Fig.16-Gate Charge Waveform




Fig.17-Typical Capacitance Vs. Drain-To-Source Voltage




Fig.18-Maximum Safe Operating Area(SOA)

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Typical Characteristics Curves




Fig.19- Normalized Maximum Transient Thermal Impedance Vs.Pulse Width

Test Circuit & Waveform





Fig.20- Inductive Switching Test Circuit & Waveform

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Test Circuit & Waveform







Fig.21-Gate Charge Test Circuit & Waveform







Fig.22- Unclamped Inductive Switching (UIS) Test Circuit & Waveform







Fig.23- Diode Recovery Test Circuit & Waveform

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT


OUTLINE DRAWINGS



TO-247

OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	15.25	-	16.75	0.6004	-	0.6594
B	20.50	-	22.50	0.8071	-	0.8858
C	4.50	-	5.10	0.1772	-	0.2008
D	0.40	-	0.80	0.0157	-	0.0315
E	3.40	-	5.00	0.1339	-	0.1969
F	1.80	-	2.50	0.0709	-	0.0984
G	2.70	-	3.30	0.1063	-	0.1299
H	1.00	-	1.40	0.0394	-	0.0551
J	5.15	-	5.75	0.2028	-	0.2264
L	18.50	-	20.50	0.7283	-	0.8071
O	2.85	-	3.15	0.1122	-	0.1240

RECOMMEDNED LAYOUT DRAWINGS



TO-247


OUTLINE DIMENSIONS						
Dim.	Milimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A	-	2.00	-	-	0.0787	-
B	-	2.00	-	-	0.0787	-
C	-	5.50	-	-	0.2165	-
D	-	1.40	-	-	0.0551	-

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

MARKING INFORMATION



MARKING INSTRUCTIONS

NH=Niuhang Trademark

FF=Product Line Code,According To Actual Changes

YWW=Date Code,According To Actual Changes

LLWWF=Inernal Code,According To Actual Changes

NCH75R260PT=Model

PACKING INFORMATION

Package Type	Package Code	Productor Weight Approx(g/Pcs)	Package Method	Quantity (Pcs/Min. Pack.)	Quantity (Pcs/Inner Box)	Quantity (Pcs/Carton)
TO-247	P1	5.778	Tube	30	600	2400

NCH75R260PT


N-Channel Silicon Carbide MOSFET

Pb Pb-Free RoHS COMPLIANT

Recommended wave soldering condition

Product	Peak Temperature	Soldering Time
Pb-free devices	260 +0/-5 °C	5 +1/-1 seconds

Recommended temperature profile for IR reflow



Profile feature	Sn-Pb eutectic Assembly	Pb-free Assembly
Average ramp-up rate (Tsmax to Tp)	3°C/second max.	3°C/second max.
Preheat−Temperature Min (TS min) −Temperature Max (TS max) −Time(ts min to ts max)	100°C 150°C 60-120 seconds	150°C 200°C 60-180 seconds
Time maintained above: −Temperature (TL) − Time (tL)	183°C 60-150 seconds	217°C 60-150 seconds
Peak Temperature(TP)	240 +0/-5 °C	260 +0/-5 °C
Time within 5°C of actual peak temperature (tp)	10-30 seconds	20-40 seconds
Ramp down rate	6°C/second max.	6°C/second max.
Time 25 °C to peak temperature	6 minutes max.	8 minutes max.

Note : All temperatures refer to topside of the package, measured on the package body surface.

Disclaimer

- Reproducing and modifying informatiom of the document is prohibited without permission from Niuhang Electronics Technology Co., LTD
- Niuhang Electronics Technology Co., LTD. reserves the rights to make changes of the content herein the document anytime without notification.
- Niuhang Electronics Technology Co., LTD. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Niuhang Electronics Technology Co., LTD. does not assume any and all implied warranties,including warranties of fitness for particular purpose,non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation.Customers are responsible in comprehending the suitable use in particular applications.Niuhang Electronics Technology Co., LTD.makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments requiring high level of reliability or relating to human life and for any applications concerning life-saving or life-sustaining,such as medical instruments.transportation equipment,aerospae machinery et cetera.Customers usin or selling these products for use in such applications do so at their own rish and agree to fully indemnify Niuhang Electronics Technology Co., LTD.for any damages resulting resulting from such improper use or sale.
- When the appearance of the product and chip size does not change, in order to product the customer. quality, change the internal structure and the production process Niuhang can not notify

NCH75R260PT

N-Channel Silicon Carbide MOSFET

Pb-Free RoHS COMPLIANT

Specification Revision History

Rev.	Date	Changed Items	Pre-Changed Content	Changed Content
A/1	2025-10-20	First Issue		
		Blank Below		